

*TYPICAL MEASUREMENTS SHOWN. EXACT DIMENSIONS DEPENDING ON OPTIONS AND TRAILER MANUFACTURER

AUXILIARY ENGINE:

Robin Subaru Manufacturer

EH-65 Model

Number of cylinders V-twin cylinder (4-cycle) 39.90 cu in (653 cc) Displacement

Compression ratio

22.0 hp @ 3,600 rpm Brake horsepower

Electric start Starting system

Fuel Gasoline; 5 gal tank capacity 1.64 qt (1500 cc) Oil filter

Charging system 12 V; 15 amp

DEBRIS HOPPER

2.0 cu yd (1.53 cu m) Volumetric capacity

Construction Impact and abrasion-resistant

polyethylene Dust separator Replaceable Separator screen Slide-in replaceable

FAN SYSTEM:

Type Radial blade Belt driven; 3V Drive

Number of blades 6

Speed 3600 rpm Diameter 20 in

Welded; abrasion-resistant steel Construction

Mounting Pillow block bearings

SWEEPING HEAD:

Debris-moving blast and suction Type

Suspension 2 trailing arms

Construction

Width 78 in (1981 mm)

Flap design 2 flaps

Tungsten Carbide Skids

10 in (254 mm) Suction hose diameter

10 in (254 mm) Pressure hose diameter Lift/Lower Manual crank winch

UNIT:

4; one at each corner Stands Curb Weight 1000 lbs (approximately)

WATER SYSTEM:

Gravity-to-intake Type Location At sweeping head; Controls Outside at water tank 25 gal (94.6 L) Tank capacity Tank construction Non-corrosive plastic

STANDARD EQUIPMENT:

Pulse-type fuel pump

Full pressure lubrication

Manual throttle & choke with remove cables

Full flow spin-on oil filter

Solenoid fuel shutdown carburetor

Cast iron cylinder sleeves

Oil pressure shut-off switch

Large dual element air cleaner Large ball bearing on PTO side

12 V electric starter with remote mount key switch

Wireless rear view camera with 7" color monitor

OPTIONAL EQUIPMENT:

Strobe light

Flood light

Mounted clean air blower

Backpack blower rack

Trailer mounted

Note: design and specifications subject to change without notice.



















Schwarze Industries. Inc. 1055 Jordan Road Huntsville, AL 35811 800.879.7933 An Alamo-Group Company






The People You Know. The Products You Trust.



SuperVac Aero™

2 Cubic Yard Portable Slide-In/Trailer Sweeper

*Sweeper shown with optional equipment



- **Polyethylene Construction**
- Clean Air Curb Blower
- 78" Reverse Sweep Pickup Head
- 22 hp Gasoline Auxiliary Engine











www.schwarze.com

800.879.7933

SuperVac Aero[™]

2 Cubic Yard Portable Slide-In/Trailer Sweeper

No butt connectors, all soldered connections: Increased uptime with the use of severe duty wiring that eliminates shorts caused by poor connections.

> Clean Air Blower: Gives operator ability to remove debris from curb line without the need for additional equipment or man hours

SILVERRUG

Financing Available

2 Yard Hopper Capacity: Larger Hopper Capacity equates to less dumping time

Heavy Duty Polyethylene Hopper: No Rust, Low Maintenance Design

AMERICAN BUILT -AMERICAN MADE

SuperVac Aero

Lighting: Warning lights placed high on unit to alert vehicles to sweeping operation



Leaf Bleeder: Allows you to exhaust up to 80% of the air. This gives the ability to better adjust the airflow based on varying material conditions

Backpack Rack: Additional storage for other equipment needed to do the Job. Keeps equipment out of the cab and easily accessible

Slide in to 1/2 Ton Pickup Truck: Eliminates the need for a dedicated piece of equipment



Computer Controlled Cutting & Forming Process: Guarantees a consistent cut part every time

Jack Stands: Provides safe and easy storage of the sweeper when not in use

Slide-Out Screen: Provides Easy Removal of Screen for Cleaning



Rear Mounted 72" Sweeping Head: Larger head contact area for debris pickup increases productivity.



Rear View Camera: Remote camera with dash mounted video monitor















*Optional Equipment Shown



Parts Availability: Schwarze original equipment parts are available when you need them.



Empowered and Responsive: Schwarze People are valued for their commitment to our future.



Schwarze Products: Engineered for enhanced performance and low ownership cost.



Warranty Support: Schwarze people are on duty to support

Schwarze parking lot sweepers are guaranteed to be free from defects due to faulty materials and / or workmanship for a period of 12 months, or 1200 hours. Liability is limited to replacement of defective parts at factory or authorized dealer. The standard warranties of the chassis and auxiliary engine manufacturer shall apply.



